

This safety data sheet was created pursuant to the requirements of: Hazardous Substances (Safety Data Sheets) Notice 2017 EPA Consolidation 30 September 2022

MARLEY CLEAR Revision Number 1 Revision date 04-Dec-2024 Supersedes date 10-Jun-2021

Section 1: Identification

Product identifier

Product Name MARLEY CLEAR

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended use Adhesives

Uses advised against No information available

Details of the supplier of the safety data sheet

<u>Supplier</u>
Bostik New Zealand Limited

<u>Manufacturer</u>
Bostik New Zealand Limited

Bostik New Zealand Limited 19 Eastern Hutt Road Wingate, Lower Hutt, New Zealand

Tel: 04-567 5119 Fax: 04-567 5412

E-mail address SDS.AP@Bostik.com

Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622

International +64 4 917 9888 Poison Centre : 0800 764 766

19 Eastern Hutt Road Wingate,

Lower Hutt, New Zealand

Tel: 04-567 5119

Fax: 04-567 5412

Section 2: Hazard identification

GHS Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3

Label elements



Signal word Danger

Hazard statements

H225 - Highly flammable liquid and vapor

New Zealand Page 1 / 13

MARLEY CLEAR
Revision Number 1
Revision date 04-Dec-2024
Supersedes date 10-Jun-2021

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Ground and bond container and receiving equipment

Use non-sparking tools

Take action to prevent static discharges

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Keep cool

Wear protective gloves

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor

Skin

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

May be harmful in contact with skin. In use, may form flammable/explosive vapor-air mixture.

Section 3: Composition/information on ingredients

)
_

Non-hazardous ingredients Proprietary Balance			
	Non-hazardous ingredients	Proprietary	Balance

Section 4: First-aid measures

Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

New Zealand Page 2 / 13

MARLEY CLEAR Revision date 04-Dec-2024 **Revision Number 1** Supersedes date 10-Jun-2021

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or

concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

> Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical attention. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or

allergic reactions see a physician.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives. Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Effects of Exposure No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

Section 5: Fire-fighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

CAUTION: Use of water spray when fighting fire may be inefficient. Large Fire

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous combustion products Carbon oxides. Hydrogen chloride.

Special protective actions for fire-fighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

New Zealand Page 3 / 13

MARLEY CLEAR
Revision Number 1
Revision date 04-Dec-2024
Supersedes date 10-Jun-2021

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containmentStop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect

vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand

or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage

Precautions for safe handling

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment. Take

off contaminated clothing and wash before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face

protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked

up. Keep out of the reach of children. Protect from moisture.

Recommended storage Keep at temperatures between $\,$ 41 and 77 $\,$ °F / 5 and 25 $\,$ °C.

New Zealand Page 4 / 13

MARLEY CLEAR
Revision Number 1

Revision date 04-Dec-2024
Supersedes date 10-Jun-2021

temperature

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Section 8: Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	New Zealand	ACGIH TLV	United Kingdom	Australia
Acetone	TWA: 500 ppm TWA: 250 ppm		TWA: 500 ppm	TWA: 500 ppm
67-64-1	TWA: 1185 mg/m ³	STEL: 500 ppm	TWA: 1210 mg/m ³	TWA: 1185 mg/m ³
	STEL: 1000 ppm		STEL: 1500 ppm	STEL: 1000 ppm
	STEL: 2375 mg/m ³		STEL: 3620 mg/m ³	STEL: 2375 mg/m ³
Methyl ethyl ketone	TWA: 150 ppm	TWA: 75 ppm	TWA: 200 ppm	TWA: 150 ppm
78-93-3	TWA: 445 mg/m ³	STEL: 150 ppm	TWA: 600 mg/m ³	TWA: 445 mg/m ³
	STEL: 300 ppm	Sk*	STEL: 300 ppm	STEL: 300 ppm
	STEL: 890 mg/m ³		STEL: 899 mg/m ³	STEL: 890 mg/m ³
	-		Sk*	-
Cyclohexanone	TWA: 25 ppm	TWA: 20 ppm	TWA: 10 ppm	TWA: 25 ppm
108-94-1	TWA: 100 mg/m ³	STEL: 50 ppm	TWA: 41 mg/m ³	TWA: 100 mg/m ³
	Sk*	Sk*	STEL: 20 ppm	-
			STEL: 82 mg/m ³	
			Sk*	

Biological occupational exposure limits

Chemical name	New Zealand	ACGIH
Acetone 50 mg/L - urine (Acetone) - end of shift 67-64-1		25 mg/L - urine (Acetone) - end of shift
Methyl ethyl ketone 78-93-3	2 mg/L - urine (MEK) - end of shift	2 mg/L - urine (MEK) - end of shift
Cyclohexanone 108-94-1	-	80 mg/L - urine (1,2-Cyclohexanediol with hydrolysis) - end of shift at end of workweek 8 mg/L - urine (Cyclohexanol with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

New Zealand Page 5 / 13

MARLEY CLEARRevision date04-Dec-2024Revision Number1Supersedes date10-Jun-2021

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid

Appearance Solution Paste Liquid
Color Clear, colorless
Odor Solvent.

Odor threshold No information available

Property Values Remarks • Method

PH No data available Not applicable Insoluble in water

Melting point / freezing point No data available None known

Initial boiling point and boiling 66 °C

range

Flash point -15 °C

Evaporation rateNo data availableNone knownFlammabilityNo data availableFlammable liquidFlammability Limit in AirNone known

Upper flammability or explosive 10.9

limits

Lower flammability or explosive 1.7

limits

Vapor pressure<110 kPa</th>None knownRelative vapor densityNo data availableNone knownRelative densityNo data availableNone known

Water solubility Insoluble in water Solubility(ies) No data available

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone known

Autoignition temperature 321 °C

Decomposition temperature

Kinematic viscosity

Dynamic viscosity

No data available

No data available

No information available.

Explosive properties No information available.

Oxidizing properties No information available.

Other information

Softening point
Molecular weight
VOC content

No information available
No information available
No information available

Liquid Density 0.9 g/cm³

Bulk density No information available

Particle characteristics

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

New Zealand Page 6 / 13

None known

None known

MARLEY CLEARRevision date04-Dec-2024Revision Number1Supersedes date10-Jun-2021

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Protect from moisture.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition

products

None known based on information supplied.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitization

by skin contact. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness

and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms

like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 6,188.00 mg/kg

 ATEmix (dermal)
 4,434.40 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-vapor)
 44.344 mg/l

 ATEmix (inhalation-dust/mist)
 >5 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	Acetone =5800 mg/kg (Rattus) 3000 mg/Kg (mouse)		=79 mg/l(Rattus) 4 h
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h

New Zealand Page 7 / 13

MARLEY CLEAR Revision Number 1

Revision date 04-Dec-2024 Supersedes date 10-Jun-2021

Cyclohexanone	=1535 mg/kg (Rattus)	= 947 mg/kg (Oryctolagus	=8000 ppm (Rattus) 4 h
		cuniculus)	
Bisphenol-A-Epichlorhydrin	LD50 (Rattus) > 2000 mg/kg	>2000 mg/Kg (Rattus)	-
Epoxy resin <= 700 MW	OECD 420		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

mnonent Information

Martha al
Acetone (67-64-1)
Component information

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye					
Irritation/Corrosion					

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitization May cause an allergic skin reaction.

Acetone (67-64-1)

Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation	Guinea pig	Dermal	Not a skin sensitizer
test			

Methyl ethyl ketone (78-93-3)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	New Zealand	IARC		
Cyclohexanone - 108-94-1	-	Group 3		

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Based on available data, the classification criteria are not met. Reproductive toxicity

May cause respiratory irritation. May cause drowsiness or dizziness. STOT - single exposure

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in					Narcotic effects
practice					

New Zealand Page 8 / 13

MARLEY CLEAR
Revision Number 1
Revision date 04-Dec-2024
Supersedes date 10-Jun-2021

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in					May cause
practice					drowsiness or
					dizziness Causes
					central nervous
					system depression

Narcotic effects Narcotic effects.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408:	Rat	Oral	200-3400 mg/kg	91 days	No Observed
Repeated Dose 90-Day			bw/day		Adverse Effect
Oral Toxicity Study in					Level LOAEL 1700
Rodents					mg/kg bw/day
Not specified	Rat	Inhalation	19000 ppm	14, 28, 56 days	NOAEC 19000 ppm
					No Observed
					Adverse Effect
					Level

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapor	1254, 2518, 5041	90 days	NOAEC 5014 ppm
Subchronic Inhalation			ppm/6h/d		
Toxicity: 90-day Study					

Aspiration hazard Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Crustacea
Acetone	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Methyl ethyl ketone	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 48 h > 308 mg/L (Daphnia magna)
Cyclohexanone	EC50: =20mg/L (96h, Chlorella vulgaris)	LC50 96 h 481 - 578 mg/L (Pimephales promelas flow-through)	EC50: =800mg/L (24h, Daphnia magna)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	2.7 mg/l 48hr Daphia Magna

Terrestrial ecotoxicity

Chemical name	Earthworm	Avian	Honeybees
Acetone	Acute Toxicity: LC50 200 -	Dietary Toxicity: LC50 >	-
	1000 μg/cm2 (Eisenia foetida,	40000 ppm (Phasianus	
	48 h filter paper)	colchicus, 5 Days)	
		Dietary Toxicity: LC50 >	

New Zealand Page 9 / 13

MARLEY CLEARRevision date04-Dec-2024Revision Number1Supersedes date10-Jun-2021

	40000 ppm (Coturnix coturnix japonica, 5 Days)	
--	--	--

Persistence and degradability

No information available.

Bioaccumulative potential Bioaccumulation Component Information

Chemical name	Partition coefficient
Acetone	-0.24
Methyl ethyl ketone	0.3
Cyclohexanone	0.86
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	3.26

Mobility in soil
Mobility

No information available.

Other adverse effects

No information available.

Disposal methods

Waste from residues/unused products

Dispose of product in packaging in a way that is consistent with the EPA Consolidation 30 April 2021 of the Hazardous Substances (Disposal) Notice 2017 and the Act. Treat the substance using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance; or export the substance from New Zealand as waste. Flammable substances - may not be disposed of into or onto a landfill or sewage facility.

They may only be burnt in certain situations.

Flammable gases, liquids and solids may only be discharged into the environment or landfill as waste if the substance will not at any time come into contact with any explosives, oxidising gases, liquids or solids or organic peroxides; and there will be no ignition source in the vicinity of the disposal site at any time and if the substance were to ignite, no person, or place where a person may legally be, would be exposed to an unsafe level of heat radiation. Substances which are hazardous to human health or corrosive to metals – may be discharged into the environment if a tolerable exposure limit has been set for the substance (or a component of that substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the tolerable exposure limit. If there is no tolerable exposure limit for the substance, then it may only be discharged into the environment if the substance is very rapidly converted to substances that are not hazardous substances.

Contaminated packaging

For packages that have been in direct contact with hazardous substances, the person must ensure that the package is rendered incapable of containing any substance. It must be disposed of in a manner that is consistent with the requirements for disposal of the substance that it contained, taking into account the material the package is manufactured from. Packages may only be reused or recycled if:

- the substance has a physical hazard other than corrosive to metal, and has been treated to remove any residual contents of the hazardous substance;
- or for substances that have a health or environmental hazard, or corrosive to metal, the contents of the residue in the package are below the threshold for the substance to be classified as hazardous in the Hazardous Substances (Hazard Classification) Notice 2020.

Section 14: Transport information

New Zealand Page 10 / 13

MARLEY CLEAR
Revision Number 1
Revision Number 1
Revision date 04-Dec-2024
Supersedes date 10-Jun-2021

IATA

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es) 3
Packing group II
Special Provisions A3

Description UN1133, Adhesives, 3, II

IMDG

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es)

Packing group

EmS-No.

Marine pollutant

3

II

F-E, S-D

NP

Description UN1133, Adhesives, 3, II, (-15°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

ADR

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es) 3
Labels 3
Packing group ||

Description UN1133, Adhesives, 3, II, (D/E)

Environmental hazards No
Limited quantity (LQ) 5 L
Special Provisions 640D
Classification code F1
Tunnel restriction code (D/E)

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EPA New Zealand HSNO approval code or group standard

HSR002662 - Surface Coatings and Colourants (Flammable)

National regulations

There are no applicable tolerable exposure limits or environmental exposure limits

according to the EPA Controls for Hazardous Substances

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information

Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please

check the Health and Safety at Work Act 2015 for further information

Controlled substance licenses are required to possess certain explosives, vertebrate toxic agents and fumigants. See Part 7 of the Health and Safety at Work Regulation 2017

for more information

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

New Zealand Page 11 / 13

MARLEY CLEARRevision date04-Dec-2024Revision Number1Supersedes date10-Jun-2021

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: Other information

Prepared By Product Safety & Regulatory Affairs

Revision date 04-Dec-2024

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk* Skin designation

** Hazard Designation + Sensitizers

C Carcinogen

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at

New Zealand Page 12 / 13

MARLEY CLEAR

Revision date 04-Dec-2024 Supersedes date 10-Jun-2021 **Revision Number** 1

the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

New Zealand Page 13 / 13